

ARQUIVO WSDL

```
<?xml version='1.0' encoding='UTF-8'?>
<definitions xmlns:wssu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
wssecurity-utility-1.0.xsd" xmlns:wsp="http://www.w3.org/ns/ws-policy"
xmlns:wsp1_2="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tns="http://crmgold.webservices.webeasy/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns="http://schemas.xmlsoap.org/wsdl/"
targetNamespace="http://crmgold.webservices.webeasy/" name="Crm">
  <types>
    <xsd:schema>
      <xs:schema xmlns:tns="http://crmgold.webservices.webeasy/"
xmlns:xs="http://www.w3.org/2001/XMLSchema" version="1.0"
targetNamespace="http://crmgold.webservices.webeasy/">

        <xs:element name="Exception" type="tns:Exception"/>

        <xs:element name="gerarEvento" type="tns:gerarEvento"/>

        <xs:element name="gerarEventoResponse"
type="tns:gerarEventoResponse"/>

        <xs:element name="getInteresses" type="tns:getInteresses"/>

        <xs:element name="getInteressesResponse"
type="tns:getInteressesResponse"/>

        <xs:element name="getMidias" type="tns:getMidias"/>

        <xs:element name="getMidiasResponse"
type="tns:getMidiasResponse"/>

        <xs:complexType name="getInteresses">
          <xs:sequence>
            <xs:element name="schema" type="xs:string"
minOccurs="0"/>
            <xs:element name="secretKey"
type="xs:string"/>
            <xs:element name="cnpjEmpresa"
type="xs:string"/>
          </xs:sequence>
        </xs:complexType>

        <xs:complexType name="getInteressesResponse">
          <xs:sequence>
            <xs:element name="return" type="xs:string"
minOccurs="0"/>
          </xs:sequence>
        </xs:complexType>
      </xs:schema>
    </xsd:schema>
  </types>
</definitions>
```

```

        </xs:sequence>
    </xs:complexType>

    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:element name="message" type="xs:string"
minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>

    <xs:complexType name="getMidias">
        <xs:sequence>
            <xs:element name="schema" type="xs:string"
minOccurs="0"/>
            <xs:element name="secretKey"
type="xs:string"/>
        </xs:sequence>
    </xs:complexType>

    <xs:complexType name="getMidiasResponse">
        <xs:sequence>
            <xs:element name="return" type="xs:string"
minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>

    <xs:complexType name="gerarEvento">
        <xs:sequence>
            <xs:element name="schema" type="xs:string"
minOccurs="0"/>
            <xs:element name="secretKey"
type="xs:string"/>
            <xs:element name="cnpjEmpresa"
type="xs:string"/>
            <xs:element name="interesse" type="xs:int"/>
            <xs:element name="nomeCliente"
type="xs:string"/>
            <xs:element name="telefone" type="xs:string"
minOccurs="0"/>
            <xs:element name="email" type="xs:string"
minOccurs="0"/>
            <xs:element name="midia" type="xs:int"
minOccurs="0"/>
            <xs:element name="mensagem"
type="xs:string" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>

    <xs:complexType name="gerarEventoResponse">

```

```

                <xs:sequence>
                    <xs:element name="return" type="xs:string"
minOccurs="0"/>
                </xs:sequence>
            </xs:complexType>
        </xs:schema>
    </xsd:schema>
</types>
<message name="gerarEvento">
    <part name="parameters" element="tns:gerarEvento"/>
</message>
<message name="gerarEventoResponse">
    <part name="parameters" element="tns:gerarEventoResponse"/>
</message>
<message name="getInteresses">
    <part name="parameters" element="tns:getInteresses"/>
</message>
<message name="getInteressesResponse">
    <part name="parameters" element="tns:getInteressesResponse"/>
</message>
<message name="Exception">
    <part name="fault" element="tns:Exception"/>
</message>
<message name="getMidias">
    <part name="parameters" element="tns:getMidias"/>
</message>
<message name="getMidiasResponse">
    <part name="parameters" element="tns:getMidiasResponse"/>
</message>
<portType name="Crm">
    <operation name="gerarEvento">
        <input wsam:Action="gerarEvento" message="tns:gerarEvento"/>
        <output
wsam:Action="http://crmgold.webservices.webeasy/Crm/gerarEventoResponse"
message="tns:gerarEventoResponse"/>
        </operation>
    <operation name="getInteresses">
        <input wsam:Action="getInteresses" message="tns:getInteresses"/>
        <output
wsam:Action="http://crmgold.webservices.webeasy/Crm/getInteressesResponse"
message="tns:getInteressesResponse"/>
        <fault message="tns:Exception" name="Exception"
wsam:Action="http://crmgold.webservices.webeasy/Crm/getInteresses/Fault/Exception"/>
        </operation>
    <operation name="getMidias">
        <input wsam:Action="getMidias" message="tns:getMidias"/>
        <output
wsam:Action="http://crmgold.webservices.webeasy/Crm/getMidiasResponse"
message="tns:getMidiasResponse"/>
    </operation>
</portType>

```

```

        <fault message="tns:Exception" name="Exception"
wsam:Action="http://crmgold.webservices.webeasy/Crm/getMidias/Fault/Exception"/>
        </operation>
    </portType>
    <binding name="CrmPortBinding" type="tns:Crm">
        <soap:binding transport="http://schemas.xmlsoap.org/soap/http"
style="document"/>
        <operation name="gerarEvento">
            <soap:operation soapAction="gerarEvento"/>
            <input>
                <soap:body use="literal"/>
            </input>
            <output>
                <soap:body use="literal"/>
            </output>
        </operation>
        <operation name="getInteresses">
            <soap:operation soapAction="getInteresses"/>
            <input>
                <soap:body use="literal"/>
            </input>
            <output>
                <soap:body use="literal"/>
            </output>
            <fault name="Exception">
                <soap:fault name="Exception" use="literal"/>
            </fault>
        </operation>
        <operation name="getMidias">
            <soap:operation soapAction="getMidias"/>
            <input>
                <soap:body use="literal"/>
            </input>
            <output>
                <soap:body use="literal"/>
            </output>
            <fault name="Exception">
                <soap:fault name="Exception" use="literal"/>
            </fault>
        </operation>
    </binding>
    <service name="Crm">
        <port name="CrmPort" binding="tns:CrmPortBinding">
            <soap:address location="http://nbs069:8400/webservices/Crm"/>
        </port>
    </service>
</definitions>

```

Exemplo de XML para consumo do getInteresses

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:crm="http://crgold.webservices.webeasy/">
  <soapenv:Header/>
  <soapenv:Body>
    <crm:getInteresses>
      <schema>NBS</schema><!--FORNECIDO PELO CLIENTE-->
      <secretKey>?</secretKey><!--FORNECIDO PELO CLIENTE-->
      <cnpjEmpresa>?</cnpjEmpresa><!--FORNECIDO PELO CLIENTE-->
    </crm:getInteresses>
  </soapenv:Body>
</soapenv:Envelope>
```

Exemplo de XML para consumo do getMidias

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:crm="http://crmgold.webservices.webeasy/">
  <soapenv:Header/>
  <soapenv:Body>
    <crm:getMidias>
      <schema>?</schema><!--Optional:-->
      <secretKey>?</secretKey>
    </crm:getMidias>
  </soapenv:Body>
</soapenv:Envelope>
```

Exemplo de XML para consumo do gerarEvento

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:crm="http://crmgold.webservices.webeasy/">
  <soapenv:Header/>
  <soapenv:Body>
    <crm:gerarEvento>
      <schema>NBS</schema> <!--FORNECIDO PELO CLIENTE-->
      <secretKey?></secretKey> <!--FORNECIDO PELO CLIENTE-->
      <cnnpjEmpresa?></cnnpjEmpresa> <!--FORNECIDO PELO CLIENTE-->
      <interesse?></interesse> <!--Ver metodo getInteresses-->
      <nomeCliente?></nomeCliente>
      <telefone?></telefone> <!--Optional: Se não enviado, deve enviar email-->
      <email?></email> <!--Optional: Se não enviado, deve enviar telefone-->
      <midia?></midia><!--Optional:-->
      <mensagem?></mensagem><!--Optional:-->
    </crm:gerarEvento>
  </soapenv:Body>
</soapenv:Envelope>
```